

trusscore Wall & Ceiling Board

Interlocking PVC panels for interior walls and ceilings



Strong & Durable

Scratch, dent, and impact resistant panels are designed to outlive the buildings they're installed in.



Lightweight & Easy to Install

Panels weigh 40% less than drywall and install 4x faster with no special tools required.



Moisture & Water Resistant

100% waterproof, won't degrade in wet or damp environments, and will never grow mold or mildew.



Washable & Easy to Clean

Can be cleaned with soap and water, chemical cleaners, and can be repeatedly pressure washed.



High Light Reflectivity

Maximize natural and fixture lighting to boost energy efficiency and make small, darker spaces appear larger.


Features & Specifications

Available in white and gray and in 8, 10, 12, 14, 16, and 20 ft lengths

- ▮ All panels are 16" wide (to match typical framing spacing) and are 1/2" thick, and have a "Class A" fire rating
- ▮ Install with any readily available wood (corrosion-resistant) screws with a minimum head diameter of 3/8"
- ▮ Install on studs or over drywall
- ▮ Pre-punched screw flange and tongue and groove interlocking system for easy installation
- ▮ Integrates seamlessly with Trusscore SlatWall for on-the-wall storage
- ▮ Lifetime Warranty (with registration)

FOLD HERE

FOLD HERE



trusscore SlatWall

PVC slatwall panels designed to organize any space



Flexible Installation

Can be installed as a track, section, half wall, or a full wall, and integrated with Trusscore Wall & Ceiling Board.



Instant Organization

Can instantly be accessorized with snap-in hooks, baskets, and shelves as soon as they're installed.



Strong & Durable

Scratch, dent, and damage resistant and are designed to hold up to 75lbs per square foot.



Moisture & Water Resistant

100% waterproof, won't degrade in wet or damp environments, and will never grow mold or mildew.



Washable & Easy to Clean

Can be cleaned with soap and water, chemical cleaners, and can be repeatedly pressure washed.

Features & Specifications

Available in white and gray and in 8 ft lengths

- ▮ Panels are 7 1/4" wide, 5/8" thick, and have a 6" exposed face and pre-punched screw flange
- ▮ Install with any readily available wood (corrosion-resistant) screws with a minimum head diameter of 3/8"
- ▮ Install on studs or over drywall
- ▮ Integrates seamlessly with Trusscore Wall & Ceiling Board; the only panel on the market to do so
- ▮ Compatible with any standard 3" slatwall accessories to meet any organizational needs
- ▮ Lifetime Warranty (with registration)